


AMENDMENT OF SOLICITATION/MODIFICATION OF CONTRACT			1. CONTRACT ID CODE	PAGE OF PAGES	
			J	1	10
2. AMENDMENT/MODIFICATION NO. P00009	3. EFFECTIVE DATE 29-Dec-2010	4. REQUISITION/PURCHASE REQ. NO. W913AD9FQYTJ21		5. PROJECT NO.(If applicable)	
6. ISSUED BY NATIONAL CAPITAL REGION CONTRACTING CTR 2461 EISENHOWER AVENUE ALEXANDRIA VA 22331-1700	CODE W91QUZ	7. ADMINISTERED BY (If other than item 6) DCMA VIRGINIA 10500 BATTLEVIEW PARKWAY, SUITE 200 MANASSAS VA 20109-2342		CODE	S2404A
8. NAME AND ADDRESS OF CONTRACTOR (No., Street, County, State and Zip Code) NORTHROP GRUMMAN INFORMATION TECHNOLOGY, 7575 COLSHIRE DR MCLEAN VA 22102-7508			9A. AMENDMENT OF SOLICITATION NO.		
			9B. DATED (SEE ITEM 11)		
			X 10A. MOD. OF CONTRACT/ORDER NO. W91QUZ-09-D-0041		
			X 10B. DATED (SEE ITEM 13) 23-Jul-2009		
CODE 1V4D7	FACILITY CODE 1V4D7				
11. THIS ITEM ONLY APPLIES TO AMENDMENTS OF SOLICITATIONS					
<input type="checkbox"/> The above numbered solicitation is amended as set forth in Item 14. The hour and date specified for receipt of Offer <input type="checkbox"/> is extended, <input type="checkbox"/> is not extended.					
<p>Offer must acknowledge receipt of this amendment prior to the hour and date specified in the solicitation or as amended by one of the following methods:</p> <p>(a) By completing Items 8 and 15, and returning _____ copies of the amendment; (b) By acknowledging receipt of this amendment on each copy of the offer submitted; or (c) By separate letter or telegram which includes a reference to the solicitation and amendment numbers. FAILURE OF YOUR ACKNOWLEDGMENT TO BE RECEIVED AT THE PLACE DESIGNATED FOR THE RECEIPT OF OFFERS PRIOR TO THE HOUR AND DATE SPECIFIED MAY RESULT IN REJECTION OF YOUR OFFER. If by virtue of this amendment you desire to change an offer already submitted, such change may be made by telegram or letter, provided each telegram or letter makes reference to the solicitation and this amendment, and is received prior to the opening hour and date specified.</p>					
12. ACCOUNTING AND APPROPRIATION DATA (If required)					
13. THIS ITEM APPLIES ONLY TO MODIFICATIONS OF CONTRACT ORDERS. IT MODIFIES THE CONTRACT/ORDER NO. AS DESCRIBED IN ITEM 14.					
A. THIS CHANGE ORDER IS ISSUED PURSUANT TO: (Specify authority) THE CHANGES SET FORTH IN ITEM 14 ARE MADE IN THE CONTRACT ORDER NO. IN ITEM 10A.					
B. THE ABOVE NUMBERED CONTRACT/ORDER IS MODIFIED TO REFLECT THE ADMINISTRATIVE CHANGES (such as changes in paying office, appropriation date, etc.) SET FORTH IN ITEM 14, PURSUANT TO THE AUTHORITY OF FAR 43.103(B).					
X C. THIS SUPPLEMENTAL AGREEMENT IS ENTERED INTO PURSUANT TO AUTHORITY OF: Part C-1(c), Changes.					
D. OTHER (Specify type of modification and authority)					
E. IMPORTANT: Contractor <input type="checkbox"/> is not, <input checked="" type="checkbox"/> is required to sign this document and return <u>1</u> copies to the issuing office.					
14. DESCRIPTION OF AMENDMENT/MODIFICATION (Organized by UCF section headings, including solicitation/contract subject matter where feasible.) Modification Control Number: gjmcgee11184 Incorporates CCP ANG004 and FM contract change APM001. See continuation pages.					
Except as provided herein, all terms and conditions of the document referenced in Item 9A or 10A, as heretofore changed, remains unchanged and in full force and effect.					
15A. NAME AND TITLE OF SIGNER (Type or print)			16A. NAME AND TITLE OF CONTRACTING OFFICER (Type or print)		
			JAMES E. JOHNSON / CONTRACTING OFFICER		
			TEL: 703-325-3430 EMAIL: james.johnson27@us.army.mil		
15B. CONTRACTOR/OFFEROR	15C. DATE SIGNED	16B. UNITED STATES OF AMERICA		16C. DATE SIGNED	
_____ (Signature of person authorized to sign)		BY 		29-Dec-2010	
		(Signature of Contracting Officer)			

AMENDMENT OF SOLICITATION/MODIFICATION OF CONTRACT			1. CONTRACT ID CODE	PAGE OF PAGES	
			J	1	10
2. AMENDMENT/MODIFICATION NO.	3. EFFECTIVE DATE	4. REQUISITION/PURCHASE REQ. NO.		5. PROJECT NO.(If applicable)	
		W913AD9FQYTJ21			
6. ISSUED BY	CODE	7. ADMINISTERED BY (If other than item 6)		CODE	
NATIONAL CAPITAL REGION CONTRACTING CTR 2461 EISENHOWER AVENUE ALEXANDRIA VA 22331-1700	W91QUZ	DCMA VIRGINIA 10500 BATTLEVIEW PARKWAY, SUITE 200 MANASSAS VA 20109-2342		S2404A	
8. NAME AND ADDRESS OF CONTRACTOR (No., Street, County, State and Zip Code)			9A. AMENDMENT OF SOLICITATION NO.		
NORTHROP GRUMMAN INFORMATION TECHNOLOGY, 7575 COLSHIRE DR MCLEAN VA 22102-7508					
			9B. DATED (SEE ITEM 11)		
			X 10A. MOD. OF CONTRACT/ORDER NO. W91QUZ-09-D-0041		
			X 10B. DATED (SEE ITEM 13) 23-Jul-2009		
CODE	FACILITY CODE				
1V4D7	1V4D7				
11. THIS ITEM ONLY APPLIES TO AMENDMENTS OF SOLICITATIONS					
<input type="checkbox"/> The above numbered solicitation is amended as set forth in Item 14. The hour and date specified for receipt of Offer <input type="checkbox"/> is extended, <input type="checkbox"/> is not extended.					
Offer must acknowledge receipt of this amendment prior to the hour and date specified in the solicitation or as amended by one of the following methods: (a) By completing Items 8 and 15, and returning _____ copies of the amendment; (b) By acknowledging receipt of this amendment on each copy of the offer submitted; or (c) By separate letter or telegram which includes a reference to the solicitation and amendment numbers. FAILURE OF YOUR ACKNOWLEDGMENT TO BE RECEIVED AT THE PLACE DESIGNATED FOR THE RECEIPT OF OFFERS PRIOR TO THE HOUR AND DATE SPECIFIED MAY RESULT IN REJECTION OF YOUR OFFER. If by virtue of this amendment you desire to change an offer already submitted, such change may be made by telegram or letter, provided each telegram or letter makes reference to the solicitation and this amendment, and is received prior to the opening hour and date specified.					
12. ACCOUNTING AND APPROPRIATION DATA (If required)					
13. THIS ITEM APPLIES ONLY TO MODIFICATIONS OF CONTRACTS/ORDERS. IT MODIFIES THE CONTRACT/ORDER NO. AS DESCRIBED IN ITEM 14.					
A. THIS CHANGE ORDER IS ISSUED PURSUANT TO: (Specify authority) THE CHANGES SET FORTH IN ITEM 14 ARE MADE IN THE CONTRACT ORDER NO. IN ITEM 10A.					
B. THE ABOVE NUMBERED CONTRACT/ORDER IS MODIFIED TO REFLECT THE ADMINISTRATIVE CHANGES (such as changes in paying office, appropriation date, etc.) SET FORTH IN ITEM 14, PURSUANT TO THE AUTHORITY OF FAR 43.103(B).					
X C. THIS SUPPLEMENTAL AGREEMENT IS ENTERED INTO PURSUANT TO AUTHORITY OF: Part C-1(c), Changes.					
D. OTHER (Specify type of modification and authority)					
E. IMPORTANT: Contractor <input type="checkbox"/> is not, <input checked="" type="checkbox"/> is required to sign this document and return <u>1</u> copies to the issuing office.					
14. DESCRIPTION OF AMENDMENT/MODIFICATION (Organized by UCF section headings, including solicitation/contract subject matter where feasible.) Modification Control Number: gjmcgee11184 Incorporates CCP ANG004 and PM contract change APM001. See continuation pages.					
Except as provided herein, all terms and conditions of the document referenced in Item 9A or 10A, as heretofore changed, remains unchanged and in full force and effect.					
15A. NAME AND TITLE OF SIGNER (Type or print)			16A. NAME AND TITLE OF CONTRACTING OFFICER (Type or print)		
Monica Kulisch, Sr. Contract Admin.					
			TEL: EMAIL:		
15B. CONTRACTOR/OFFEROR	15C. DATE SIGNED	16B. UNITED STATES OF AMERICA		16C. DATE SIGNED	
<i>Monica Kulisch</i> (Signature of person authorized to sign)	12/20/10	BY _____ (Signature of Contracting Officer)			

EXCEPTION TO SF 30  
APPROVED BY OIRM 11-84

30-105-04

STANDARD FORM 30 (Rev. 10-83)  
Prescribed by GSA  
FAR (48 CFR) 53.243

## SECTION SF 30 BLOCK 14 CONTINUATION PAGE

**The following items are applicable to this modification:**SF 30 CONT'D

A. This modification incorporates Contract Change Proposal (CCP) No. ANG004 and PM J-AIT contract change APM001, and corrects the description for SLIN 1009FA.

1. As a result of incorporation of CCP No. ANG004, SLIN descriptions are changed as shown in **red** font in the following table:

SLIN	Description – FROM	Description – TO
0001CB 1001CB	HHT-C Holster and Shoulder Strap (Motorola P/N:SG-MC90212110-01R) and HHT Shoulder Strap (Motorola P/N:58-40000-007R)	HHT-C Holster and Shoulder Strap (Motorola P/N: <b>SG-MC9121112-01R</b> ) and HHT Shoulder Strap (Motorola P/N:58-40000-007R)
0001DB 1001DB	HHT-D Holster and Shoulder Strap (Motorola P/N:SG-MC90212110-01R) and HHT Shoulder Strap (Motorola P/N:SG-MC90212110-01R)	HHT-D Holster and Shoulder Strap (Motorola P/N: <b>SG-MC9121112-01R</b> ) and HHT Shoulder Strap (Motorola P/N:SG-MC90212110-01R)
0001EB 1001EB	HHT-E Holster and Shoulder Strap (Motorola P/N:58-40000-007R)	HHT-E Holster ( <b>Motorola P/N SG-MC9121112-01R</b> ) and HHT Shoulder Strap (Motorola P/N:58-40000-007R)
0001FB 1001FB	HHT-F Holster and Shoulder Strap Motorola P/N:SG-MC90212110-01R) and HHT Shoulder Strap (Motorola P/N:58-40000-007R)	HHT-F Holster and Shoulder Strap Motorola P/N: <b>SG-MC9121112-01R</b> ) and HHT Shoulder Strap (Motorola P/N:58-40000-007R)

2. As a result of incorporation of PM J-AIT contract change APM001, the following informational notes are administratively added to SLIN descriptions as shown in the following table.

SLIN	Information Note – Added
0001AA 1001AA	NOTE: Naval Surface Warfare Center, Dahlgren tested for Hazards of Electromagnetic Radiation to Ordnance (HERO) and the recommended safe distance separation is 0 inches.
0001CA 1001CA	NOTE: Naval Surface Warfare Center, Dahlgren tested for Hazards of Electromagnetic Radiation to Ordnance (HERO) and the recommended safe distance separation is 6 inches.
0001EA 1001EA	NOTE: Naval Surface Warfare Center, Dahlgren tested for Hazards of Electromagnetic Radiation to Ordnance (HERO) and the recommended safe distance separation is 6 inches.
0001FA 1001FA	NOTE: Naval Surface Warfare Center, Dahlgren tested for Hazards of Electromagnetic Radiation to Ordnance (HERO) and the recommended safe distance separation is 6 inches
0009EA 1009EA	NOTE: Naval Surface Warfare Center, Dahlgren tested for Hazards of Electromagnetic Radiation to Ordnance (HERO) and the recommended safe distance separation is 12 inches
0009FA 1009FA	NOTE: Naval Surface Warfare Center, Dahlgren tested for Hazards of Electromagnetic Radiation to Ordnance (HERO) and the recommended safe distance separation is 12 inches.
0015AA 1015AA	NOTE: Naval Surface Warfare Center, Dahlgren tested for Hazards of Electromagnetic Radiation to Ordnance (HERO) and the recommended safe distance separation is 14 inches.
0015BA 1015BA	NOTE: Naval Surface Warfare Center, Dahlgren tested for Hazards of Electromagnetic Radiation to Ordnance (HERO) and the recommended safe distance separation is 14 inches.
0015CA 1015CA	NOTE: Naval Surface Warfare Center, Dahlgren tested for Hazards of Electromagnetic Radiation to Ordnance (HERO) and the recommended safe distance separation is 14 inches.

3. SLIN 1009FA: Modification P00005 changed the description for SLIN 0009FA. However, corresponding change to SLIN 1009FA was inadvertently omitted from that modification. In addition to adding the NOTE above, this modification changes SLIN 1009FA's description to conform to SLIN 0009FA's description as follows:

FROM: Stationary Bar Code and Gen2 RFID Label Printer/Encoder (Zebra P/N:RZ47D-2001-00R0)

TO: Stationary Bar Code and Gen2 RFID Label Printer/Encoder (Zebra P/N:123-100256)

B. As a result of this modification, there is no change in the total amount obligated under the contract.

C. All other terms and conditions are unchanged.

## SUMMARY OF CHANGES

### SECTION SF 1449 - CONTINUATION SHEET

#### SUPPLIES OR SERVICES AND PRICES

##### SUBCLIN 0001AA

The CLIN extended description has changed from Hand Held Barcode Terminal (HHT-A) with Abbreviated Keypad and Wireless (802.11g/i) Communications, Hand Held Barcode Terminal (HHT-A) with Abbreviated Keypad and Wireless (802.11g/i) Communications includes: HHT-A (Motorola P/N:MC9090-KK0HCFQA660), [Communication Docking Kit: Comm Dock/Battery Charger with USB interface, AC Adapter, AC Line Cord (Motorola P/N:CRD9000-110SR)], USB Cable for the cradle to the host system (Motorola P/N:25-64396-01R), CAC Reader (Apriva P/N:BT200-T), CAC Enablement Software SensaCSPware (Apriva P/N:SENSACSPWARE-CLIENT-1000), CAC Enablement Software SensaGuard (Apriva P/N:SENSAGUARD-CLIENT-1000), Data at rest/Malicious code/Firewall software (Symantec P/N:SYMC-MOBILE-BUNDLE), FIPS 140-2 Client (HHT) (Juniper P/N:OAC-ADD-F1CLT), Spare Lithium Battery (Motorola P/N:KT-21-61261-01), Spare Stylus (3 per package) (Motorola P/N:KT-81680-03R), 2 GB Memory Media - Bartec Industrial NI certified SD/MMC (Bartec P/N:17-28BE-F006/003) to Hand Held Barcode Terminal (HHT-A) with Abbreviated Keypad and Wireless (802.11g/i) Communications, Hand Held Barcode Terminal (HHT-A) with Abbreviated Keypad and Wireless (802.11g/i) Communications includes: HHT-A (Motorola P/N:MC9090-KK0HCFQA660), [Communication Docking Kit: Comm Dock/Battery Charger with USB interface, AC Adapter, AC Line Cord (Motorola P/N:CRD9000-110SR)], USB Cable for the cradle to the host system (Motorola P/N:25-64396-01R), CAC Reader (Apriva P/N:BT200-T), CAC Enablement Software SensaCSPware (Apriva P/N:SENSACSPWARE-CLIENT-1000), CAC Enablement Software SensaGuard (Apriva P/N:SENSAGUARD-CLIENT-1000), Data at rest/Malicious code/Firewall software (Symantec P/N:SYMC-MOBILE-BUNDLE), FIPS 140-2 Client (HHT) (Juniper P/N:OAC-ADD-F1CLT), Spare Lithium Battery (Motorola P/N:KT-21-61261-01), Spare Stylus (3 per package) (Motorola P/N:KT-81680-03R), 2 GB Memory Media - Bartec Industrial NI certified SD/MMC (Bartec P/N:17-28BE-F006/003) NOTE: Naval Surface Warfare Center, Dahlgren tested for Hazards of Electromagnetic Radiation to Ordnance (HERO) and the recommended safe distance separation is 0 inches..

##### SUBCLIN 0001CA

The CLIN extended description has changed from Hand Held Barcode Terminal (HHT-C) with Full Alpha-numeric Keypad and Wireless (802.11g/i) Communications, and Win Mobile 6.x Installed, includes: HHT-C (Motorola P/N:MC9090-GK0HCEQA6WR), [Communication Docking Kit: Comm Dock/Battery Charger with

USB interface, AC Adapter, AC Line Cord (Motorola P/N:CRD9000-110SR)], USB cable for the Cradle to the Host System (Motorola P/N:25-64396-01R), CAC Reader (Apriva P/N:BT200-T), CAC Enablement Software SensaCSPware (Apriva P/N:SENSACSPWARE-CLIENT-1000), CAC Enablement Software SensaGuard (Apriva P/N:SENSAGUARD-CLIENT-1000), Data at rest/Malicious code/Firewall software (Symantec P/N:SYMC-MOBILE-BUNDLE), FIPS 140-2 Client (HHT) (Juniper P/N:OAC-ADD-F1CLT), Spare Lithium Battery (Motorola P/N:KT-21-61261-01), Spare Stylus (3 per package) (Motorola P/N:KT-81680-03R), 2 GB Memory Media - Bartec Industrial NI certified SD/MMC (Bartec P/N:17-28BE-F006/003) to Hand Held Barcode Terminal (HHT-C) with Full Alpha-numeric Keypad and Wireless (802.11g/i) Communications, and Win Mobile 6.x Installed, includes: HHT-C (Motorola P/N:MC9090-GK0HCEQA6WR), [Communication Docking Kit: Comm Dock/Battery Charger with USB interface, AC Adapter, AC Line Cord (Motorola P/N:CRD9000-110SR)], USB cable for the Cradle to the Host System (Motorola P/N:25-64396-01R), CAC Reader (Apriva P/N:BT200-T), CAC Enablement Software SensaCSPware (Apriva P/N:SENSACSPWARE-CLIENT-1000), CAC Enablement Software SensaGuard (Apriva P/N:SENSAGUARD-CLIENT-1000), Data at rest/Malicious code/Firewall software (Symantec P/N:SYMC-MOBILE-BUNDLE), FIPS 140-2 Client (HHT) (Juniper P/N:OAC-ADD-F1CLT), Spare Lithium Battery (Motorola P/N:KT-21-61261-01), Spare Stylus (3 per package) (Motorola P/N:KT-81680-03R), 2 GB Memory Media - Bartec Industrial NI certified SD/MMC (Bartec P/N:17-28BE-F006/003) NOTE: Naval Surface Warfare Center, Dahlgren tested for Hazards of Electromagnetic Radiation to Ordnance (HERO) and the recommended safe distance separation is 6 inches..

#### SUBCLIN 0001CB

The CLIN extended description has changed from HHT-C Holster and Shoulder Strap (Motorola P/N:SG-MC90212110-01R) and HHT Shoulder Strap (Motorola P/N:58-40000-007R) to HHT-C Holster and Shoulder Strap (Motorola P/N:SG-MC9121112-01R) and HHT Shoulder Strap (Motorola P/N:58-40000-007R).

#### SUBCLIN 0001DB

The CLIN extended description has changed from HHT-D Holster and Shoulder Strap (Motorola P/N:SG-MC90212110-01R) and HHT Shoulder Strap (Motorola P/N:SG-MC90212110-01R) to HHT-D Holster and Shoulder Strap (Motorola P/N:SG-MC9121112-01R) and HHT Shoulder Strap (Motorola P/N:SG-MC90212110-01R).

#### SUBCLIN 0001EA

The CLIN extended description has changed from Hand Held Barcode Terminal (HHT-E) with Extended Reading Range, Full Alpha-numeric Keypad, and Wireless (802.11g/i) Communications (Desired - Reference Part D, paragraph 4.1.6) includes: HHT-E (Motorola P/N:MC9090-GJ0HCEQA6WR), [Communication Docking Kit: Comm Dock/Battery Charger with USB interface, AC Adapter, AC Line Cord (Motorola P/N:CRD9000-110SR)], USB cable for the Cradle to the Host System (Motorola P/N:25-64396-01R), CAC Reader (Apriva P/N:BT200-T), CAC Enablement Software SensaCSPware (Apriva P/N:SENSACSPWARE-CLIENT-1000), CAC Enablement Software SensaGuard (Apriva P/N:SENSAGUARD-CLIENT-1000), Data at rest/Malicious code/Firewall software (Symantec P/N:SYMC-MOBILE-BUNDLE), FIPS 140-2 Client (HHT) (Juniper P/N:OAC-ADD-F1CLT), Spare Lithium Battery (Motorola P/N:KT-21-61261-01), Spare Stylus(3 per package) (Motorola P/N:KT-81680-03R), 2 GB Memory Media - Bartec Industrial NI certified SD/MMC (Bartec P/N:17-28BE-F006/003 ) to Hand Held Barcode Terminal (HHT-E) with Extended Reading Range, Full Alpha-numeric Keypad, and Wireless (802.11g/i) Communications (Desired - Reference Part D, paragraph 4.1.6) includes: HHT-E (Motorola P/N:MC9090-GJ0HCEQA6WR), [Communication Docking Kit: Comm Dock/Battery Charger with USB interface, AC Adapter, AC Line Cord (Motorola P/N:CRD9000-110SR)], USB cable for the Cradle to the Host System (Motorola P/N:25-64396-01R), CAC Reader (Apriva P/N:BT200-T), CAC Enablement Software SensaCSPware (Apriva P/N:SENSACSPWARE-CLIENT-1000), CAC Enablement Software SensaGuard (Apriva P/N:SENSAGUARD-CLIENT-1000), Data at rest/Malicious code/Firewall software (Symantec P/N:SYMC-MOBILE-BUNDLE), FIPS 140-2 Client (HHT) (Juniper P/N:OAC-ADD-F1CLT), Spare Lithium Battery (Motorola P/N:KT-21-61261-01),

Spare Stylus(3 per package) (Motorola P/N:KT-81680-03R), 2 GB Memory Media - Bartec Industrial NI certified SD/MMC (Bartec P/N:17-28BE-F006/003) NOTE: Naval Surface Warfare Center, Dahlgren tested for Hazards of Electromagnetic Radiation to Ordnance (HERO) and the recommended safe distance separation is 6 inches..

#### SUBCLIN 0001EB

The CLIN extended description has changed from HHT-E Holster and Shoulder Strap (Motorola P/N:58-40000-007R) to HHT-E Holster (Motorola P/N SG-MC9121112-01R) and HHT Shoulder Strap (Motorola P/N:58-40000-007R).

#### SUBCLIN 0001FA

The CLIN extended description has changed from Hand Held Barcode Terminal (HHT-F) with Direct Part Mark Reading Capability, Full Alpha-numeric Keypad, and Wireless (802.11g/i) Communications includes: HHT-F (Motorola P/N:MC9090-GW0HJEA6WR), [Communication Docking Kit: Comm Dock/Battery Charger with USB interface, AC Adapter, AC Line Cord (Motorola P/N:CRD9000-110SR)], USB cable for the Cradle to the Host System (Motorola P/N:25-64396-01R), CAC Reader (Apriva P/N:BT200-T), CAC Enablement Software SensaCSPware (Apriva P/N:SENSACSPWARE-CLIENT-1000), CAC Enablement Software SensaGuard (Apriva P/N:SENSAGUARD-CLIENT-1000), Data at rest/Malicious code/Firewall software (Symantec P/N:SYMC-MOBILE-BUNDLE), FIPS 140-2 Client (HHT) (Juniper P/N:OAC-ADD-F1CLT), Spare Lithium Battery (Motorola P/N:KT-21-61261-01), Spare Stylus (3 per package) (Motorola P/N:KT-81680-03R), 2 GB Memory Media - Bartec Industrial NI certified SD/MMC (Bartec P/N:17-28BE-F006/003) to Hand Held Barcode Terminal (HHT-F) with Direct Part Mark Reading Capability, Full Alpha-numeric Keypad, and Wireless (802.11g/i) Communications includes: HHT-F (Motorola P/N:MC9090-GW0HJEA6WR), [Communication Docking Kit: Comm Dock/Battery Charger with USB interface, AC Adapter, AC Line Cord (Motorola P/N:CRD9000-110SR)], USB cable for the Cradle to the Host System (Motorola P/N:25-64396-01R), CAC Reader (Apriva P/N:BT200-T), CAC Enablement Software SensaCSPware (Apriva P/N:SENSACSPWARE-CLIENT-1000), CAC Enablement Software SensaGuard (Apriva P/N:SENSAGUARD-CLIENT-1000), Data at rest/Malicious code/Firewall software (Symantec P/N:SYMC-MOBILE-BUNDLE), FIPS 140-2 Client (HHT) (Juniper P/N:OAC-ADD-F1CLT), Spare Lithium Battery (Motorola P/N:KT-21-61261-01), Spare Stylus (3 per package) (Motorola P/N:KT-81680-03R), 2 GB Memory Media - Bartec Industrial NI certified SD/MMC (Bartec P/N:17-28BE-F006/003) NOTE: Naval Surface Warfare Center, Dahlgren tested for Hazards of Electromagnetic Radiation to Ordnance (HERO) and the recommended safe distance separation is 6 inches..

#### SUBCLIN 0001FB

The CLIN extended description has changed from HHT-F Holster and Shoulder Strap Motorola P/N:SG-MC90212110-01R) and HHT Shoulder Strap (Motorola P/N:58-40000-007R) to HHT-F Holster and Shoulder Strap Motorola P/N:SG-MC9121112-01R) and HHT Shoulder Strap (Motorola P/N:58-40000-007R).

#### SUBCLIN 0009EA

The CLIN extended description has changed from Stationary Bar Code Label Printer with 802.11g/i Wireless Communications (Zebra P/N:123-100255 to Stationary Bar Code Label Printer with 802.11g/i Wireless Communications (Zebra P/N:123-100255)NOTE: Naval Surface Warfare Center, Dahlgren tested for Hazards of Electromagnetic Radiation to Ordnance (HERO) and the recommended safe distance separation is 12 inches..

#### SUBCLIN 0009FA

The CLIN extended description has changed from Stationary Bar Code and Gen2 RFID Label

Printer/Encoder (Zebra P/N:123-100256) to Stationary Bar Code and Gen2 RFID Label Printer/Encoder (Zebra P/N:123-100256) NOTE: Naval Surface Warfare Center, Dahlgren tested for Hazards of Electromagnetic Radiation to Ordnance (HERO) and the recommended safe distance separation is 12 inches..

#### SUBCLIN 0015AA

The CLIN extended description has changed from Radio Frequency Access Point (indoor environment) includes: AP-7131 Dual Radio 802.11a/g Access Point (Motorola P/N:AP-7131N-44040-FGR ), [AP-7131 Power Supply: 100- 250VAC,48.0VDC, 0.75A (Motorola P/N: 50-14000-247R )], AC Line Cord (Motorola P/N: 50-16000-221R ), [Antenna: Indoor; Type: Dipole; 3dBi @2.4GHz (Motorola P/N: ML-2452-AP2-01)] to Radio Frequency Access Point (indoor environment) includes: AP-7131 Dual Radio 802.11a/g Access Point (Motorola P/N:AP-7131N-44040-FGR ), [AP-7131 Power Supply: 100- 250VAC,48.0VDC, 0.75A (Motorola P/N: 50-14000-247R )], AC Line Cord (Motorola P/N: 50-16000-221R ), [Antenna: Indoor; Type: Dipole; 3dBi @2.4GHz (Motorola P/N: ML-2452-AP2-01)] NOTE: Naval Surface Warfare Center, Dahlgren tested for Hazards of Electromagnetic Radiation to Ordnance (HERO) and the recommended safe distance separation is 14 inches..

#### SUBCLIN 0015BA

The CLIN extended description has changed from Radio Frequency Access Point (NEMA Enclosure) includes: AP-7131 Dual Radio 802.11a/g Access Point (Motorola P/N:AP-7131N-44040-FGR ), [AP-7131 Power Supply: 100- 250VAC,48.0VDC, 0.75A (Motorola P/N: 50-14000-247R )], AC Line Cord (Motorola P/N: 50-16000-221R ), NEMA Enclosure (TESSCO P/N:V14126-C60-C-6), RP-SMA (Male) to RP-BNC (Female) Adapter (Motorola P/N:25-72178-01), [Antenna: Indoor/Outdoor; Type: Dipole; 4.6dBi (Motorola P/N:ML-2499-HPA3-01R)] to Radio Frequency Access Point (NEMA Enclosure) includes: AP-7131 Dual Radio 802.11a/g Access Point (Motorola P/N:AP-7131N-44040-FGR ), [AP-7131 Power Supply: 100- 250VAC,48.0VDC, 0.75A (Motorola P/N: 50-14000-247R )], AC Line Cord (Motorola P/N: 50-16000-221R ), NEMA Enclosure (TESSCO P/N:V14126-C60-C-6), RP-SMA (Male) to RP-BNC (Female) Adapter (Motorola P/N:25-72178-01), [Antenna: Indoor/Outdoor; Type: Dipole; 4.6dBi (Motorola P/N:ML-2499-HPA3-01R)] NOTE: Naval Surface Warfare Center, Dahlgren tested for Hazards of Electromagnetic Radiation to Ordnance (HERO) and the recommended safe distance separation is 14 inches..

#### SUBCLIN 0015CA

The CLIN extended description has changed from Radio Frequency Gateway includes: AP-7131 Dual Radio 802.11a/g Access Point (Motorola P/N:AP-7131N-44040-FGR ), [AP-7131 Power Supply: 100- 250VAC,48.0VDC, 0.75A (Motorola P/N: 50-14000-247R )], AC Line Cord (Motorola P/N: 50-16000-221R ), RFMS Server Software (includes LANPlanner) (Motorola P/N:SW-RFMS-SRV-050-WW ), [Antenna: Indoor; Type: Dipole; 3dBi @2.4GHz (Motorola P/N:ML-2452-APA2-01 )] to Radio Frequency Gateway includes: AP-7131 Dual Radio 802.11a/g Access Point (Motorola P/N:AP-7131N-44040-FGR ), [AP-7131 Power Supply: 100- 250VAC,48.0VDC, 0.75A (Motorola P/N: 50-14000-247R )], AC Line Cord (Motorola P/N: 50-16000-221R ), RFMS Server Software (includes LANPlanner) (Motorola P/N:SW-RFMS-SRV-050-WW ), [Antenna: Indoor; Type: Dipole; 3dBi @2.4GHz (Motorola P/N:ML-2452-APA2-01)] NOTE: Naval Surface Warfare Center, Dahlgren tested for Hazards of Electromagnetic Radiation to Ordnance (HERO) and the recommended safe distance separation is 14 inches..

#### SUBCLIN 1001AA

The CLIN extended description has changed from Hand Held Barcode Terminal (HHT-A) with Abbreviated Keypad and Wireless (802.11g/i) Communications, Hand Held Barcode Terminal (HHT-A) with Abbreviated Keypad and Wireless (802.11g/i) Communications includes: HHT-A (Motorola P/N:MC9090-KK0HCFQA660), [Communication Docking Kit: Comm Dock/Battery Charger with USB interface, AC Adapter,

AC Line Cord (Motorola P/N:CRD9000-110SR)], USB Cable for the cradle to the host system (Motorola P/N:25-64396-01R), CAC Reader (Apriva P/N:BT200-T), CAC Enablement Software SensaCSPware (Apriva P/N:SENSACSPWARE-CLIENT-1000), CAC Enablement Software SensaGuard (Apriva P/N:SENSAGUARD-CLIENT-1000), Data at rest/Malicious code/Firewall software (Symantec P/N:SYMC-MOBILE-BUNDLE), FIPS 140-2 Client (HHT) (Juniper P/N:OAC-ADD-F1CLT), Spare Lithium Battery (Motorola P/N:KT-21-61261-01), Spare Stylus (3 per package) (Motorola P/N:KT-81680-03R), 2 GB Memory Media - Bartec Industrial NI certified SD/MMC (Bartec P/N:17-28BE-F006/003) to Hand Held Barcode Terminal (HHT-A) with Abbreviated Keypad and Wireless (802.11g/i) Communications, Hand Held Barcode Terminal (HHT-A) with Abbreviated Keypad and Wireless (802.11g/i) Communications includes: HHT-A (Motorola P/N:MC9090- KK0HCFQA660), [Communication Docking Kit: Comm Dock/Battery Charger with USB interface, AC Adapter, AC Line Cord (Motorola P/N:CRD9000-110SR)], USB Cable for the cradle to the host system (Motorola P/N:25-64396-01R), CAC Reader (Apriva P/N:BT200-T), CAC Enablement Software SensaCSPware (Apriva P/N:SENSACSPWARE-CLIENT-1000), CAC Enablement Software SensaGuard (Apriva P/N:SENSAGUARD-CLIENT-1000), Data at rest/Malicious code/Firewall software (Symantec P/N:SYMC-MOBILE-BUNDLE), FIPS 140-2 Client (HHT) (Juniper P/N:OAC-ADD-F1CLT), Spare Lithium Battery (Motorola P/N:KT-21-61261-01), Spare Stylus (3 per package) (Motorola P/N:KT-81680-03R), 2 GB Memory Media - Bartec Industrial NI certified SD/MMC (Bartec P/N:17-28BE-F006/003) NOTE: Naval Surface Warfare Center, Dahlgren tested for Hazards of Electromagnetic Radiation to Ordnance (HERO) and the recommended safe distance separation is 0 inches..

#### SUBCLIN 1001CA

The CLIN extended description has changed from Hand Held Barcode Terminal (HHT-C) with Full Alpha-numeric Keypad and Wireless (802.11g/i) Communications, and Win Mobile 6.x Installed, includes: HHT-C (Motorola P/N:MC9090-GK0HCEQA6WR), [Communication Docking Kit: Comm Dock/Battery Charger with USB interface, AC Adapter, AC Line Cord (Motorola P/N:CRD9000-110SR)], USB cable for the Cradle to the Host System (Motorola P/N:25-64396-01R), CAC Reader (Apriva P/N:BT200-T), CAC Enablement Software SensaCSPware (Apriva P/N:SENSACSPWARE-CLIENT-1000), CAC Enablement Software SensaGuard (Apriva P/N:SENSAGUARD-CLIENT-1000), Data at rest/Malicious code/Firewall software (Symantec P/N:SYMC-MOBILE-BUNDLE), FIPS 140-2 Client (HHT) (Juniper P/N:OAC-ADD-F1CLT), Spare Lithium Battery (Motorola P/N:KT-21-61261-01), Spare Stylus (3 per package) (Motorola P/N:KT-81680-03R), 2 GB Memory Media - Bartec Industrial NI certified SD/MMC (Bartec P/N:17-28BE-F006/003) to Hand Held Barcode Terminal (HHT-C) with Full Alpha-numeric Keypad and Wireless (802.11g/i) Communications, and Win Mobile 6.x Installed, includes: HHT-C (Motorola P/N:MC9090-GK0HCEQA6WR), [Communication Docking Kit: Comm Dock/Battery Charger with USB interface, AC Adapter, AC Line Cord (Motorola P/N:CRD9000-110SR)], USB cable for the Cradle to the Host System (Motorola P/N:25-64396-01R), CAC Reader (Apriva P/N:BT200-T), CAC Enablement Software SensaCSPware (Apriva P/N:SENSACSPWARE-CLIENT-1000), CAC Enablement Software SensaGuard (Apriva P/N:SENSAGUARD-CLIENT-1000), Data at rest/Malicious code/Firewall software (Symantec P/N:SYMC-MOBILE-BUNDLE), FIPS 140-2 Client (HHT) (Juniper P/N:OAC-ADD-F1CLT), Spare Lithium Battery (Motorola P/N:KT-21-61261-01), Spare Stylus (3 per package) (Motorola P/N:KT-81680-03R), 2 GB Memory Media - Bartec Industrial NI certified SD/MMC (Bartec P/N:17-28BE-F006/003) NOTE: Naval Surface Warfare Center, Dahlgren tested for Hazards of Electromagnetic Radiation to Ordnance (HERO) and the recommended safe distance separation is 6 inches..

#### SUBCLIN 1001CB

The CLIN extended description has changed from HHT-C Holster and Shoulder Strap (Motorola P/N:SG-MC90212110-01R) and HHT Shoulder Strap (Motorola P/N:58-40000-007R) to HHT-C Holster and Shoulder Strap (Motorola P/N:SG-MC9121112-01R) and HHT Shoulder Strap (Motorola P/N:58-40000-007R).

#### SUBCLIN 1001EA

The CLIN extended description has changed from Hand Held Barcode Terminal (HHT-E) with Extended

Reading Range, Full Alpha-numeric Keypad, and Wireless (802.11g/i) Communications (Desired - Reference Part D, paragraph 4.1.6) includes: HHT-E (Motorola P/N:MC9090-GJ0HCEQA6WR), [Communication Docking Kit: Comm Dock/Battery Charger with USB interface, AC Adapter, AC Line Cord (Motorola P/N:CRD9000-110SR)], USB cable for the Cradle to the Host System (Motorola P/N:25-64396-01R), CAC Reader (Apriva P/N:BT200-T), CAC Enablement Software SensaCSPware (Apriva P/N:SENSACSPWARE-CLIENT-1000), CAC Enablement Software SensaGuard (Apriva P/N:SENSAGUARD-CLIENT-1000), Data at rest/Malicious code/Firewall software (Symantec P/N:SYMC-MOBILE-BUNDLE), FIPS 140-2 Client (HHT) (Juniper P/N:OAC-ADD-F1CLT), Spare Lithium Battery (Motorola P/N:KT-21-61261-01), Spare Stylus(3 per package) (Motorola P/N:KT-81680-03R), 2 GB Memory Media - Bartec Industrial NI certified SD/MMC (Bartec P/N:17-28BE-F006/003 ) to Hand Held Barcode Terminal (HHT-E) with Extended Reading Range, Full Alpha-numeric Keypad, and Wireless (802.11g/i) Communications (Desired - Reference Part D, paragraph 4.1.6) includes: HHT-E (Motorola P/N:MC9090-GJ0HCEQA6WR), [Communication Docking Kit: Comm Dock/Battery Charger with USB interface, AC Adapter, AC Line Cord (Motorola P/N:CRD9000-110SR)], USB cable for the Cradle to the Host System (Motorola P/N:25-64396-01R), CAC Reader (Apriva P/N:BT200-T), CAC Enablement Software SensaCSPware (Apriva P/N:SENSACSPWARE-CLIENT-1000), CAC Enablement Software SensaGuard (Apriva P/N:SENSAGUARD-CLIENT-1000), Data at rest/Malicious code/Firewall software (Symantec P/N:SYMC-MOBILE-BUNDLE), FIPS 140-2 Client (HHT) (Juniper P/N:OAC-ADD-F1CLT), Spare Lithium Battery (Motorola P/N:KT-21-61261-01), Spare Stylus(3 per package) (Motorola P/N:KT-81680-03R), 2 GB Memory Media - Bartec Industrial NI certified SD/MMC (Bartec P/N:17-28BE-F006/003) NOTE: Naval Surface Warfare Center, Dahlgren tested for Hazards of Electromagnetic Radiation to Ordnance (HERO) and the recommended safe distance separation is 6 inches..

#### SUBCLIN 1001EB

The CLIN extended description has changed from HHT-E Holster and Shoulder Strap (Motorola P/N:58-40000-007R) to HHT-E Holster (Motorola P/N SG-MC9121112-01R) and HHT Shoulder Strap (Motorola P/N:58-40000-007R).

#### SUBCLIN 1001FA

The CLIN extended description has changed from Hand Held Barcode Terminal (HHT-F) with Direct Part Mark Reading Capability, Full Alpha-numeric Keypad, and Wireless (802.11g/i) Communications includes: HHT-F (Motorola P/N:MC9090-GW0HJEQA6WR), [Communication Docking Kit: Comm Dock/Battery Charger with USB interface, AC Adapter, AC Line Cord (Motorola P/N:CRD9000-110SR)], USB cable for the Cradle to the Host System (Motorola P/N:25-64396-01R), CAC Reader (Apriva P/N:BT200-T), CAC Enablement Software SensaCSPware (Apriva P/N:SENSACSPWARE-CLIENT-1000), CAC Enablement Software SensaGuard (Apriva P/N:SENSAGUARD-CLIENT-1000), Data at rest/Malicious code/Firewall software (Symantec P/N:SYMC-MOBILE-BUNDLE), FIPS 140-2 Client (HHT) (Juniper P/N:OAC-ADD-F1CLT), Spare Lithium Battery (Motorola P/N:KT-21-61261-01), Spare Stylus (3 per package) (Motorola P/N:KT-81680-03R), 2 GB Memory Media - Bartec Industrial NI certified SD/MMC (Bartec P/N:17-28BE-F006/003) to Hand Held Barcode Terminal (HHT-F) with Direct Part Mark Reading Capability, Full Alpha-numeric Keypad, and Wireless (802.11g/i) Communications includes: HHT-F (Motorola P/N:MC9090-GW0HJEQA6WR), [Communication Docking Kit: Comm Dock/Battery Charger with USB interface, AC Adapter, AC Line Cord (Motorola P/N:CRD9000-110SR)], USB cable for the Cradle to the Host System (Motorola P/N:25-64396-01R), CAC Reader (Apriva P/N:BT200-T), CAC Enablement Software SensaCSPware (Apriva P/N:SENSACSPWARE-CLIENT-1000), CAC Enablement Software SensaGuard (Apriva P/N:SENSAGUARD-CLIENT-1000), Data at rest/Malicious code/Firewall software (Symantec P/N:SYMC-MOBILE-BUNDLE), FIPS 140-2 Client (HHT) (Juniper P/N:OAC-ADD-F1CLT), Spare Lithium Battery (Motorola P/N:KT-21-61261-01), Spare Stylus (3 per package) (Motorola P/N:KT-81680-03R), 2 GB Memory Media - Bartec Industrial NI certified SD/MMC (Bartec P/N:17-28BE-F006/003) NOTE: Naval Surface Warfare Center, Dahlgren tested for Hazards of Electromagnetic Radiation to Ordnance (HERO) and the recommended safe distance separation is 6 inches..

**SUBCLIN 1001FB**

The CLIN extended description has changed from HHT-F Holster and Shoulder Strap Motorola P/N:SG-MC90212110-01R) and HHT Shoulder Strap (Motorola P/N:58-40000-007R) to HHT-F Holster and Shoulder Strap Motorola P/N:SG-MC9121112-01R) and HHT Shoulder Strap (Motorola P/N:58-40000-007R).

**SUBCLIN 1009EA**

The CLIN extended description has changed from Stationary Bar Code Label Printer with 802.11g/i Wireless Communications (Zebra P/N:123-100255 to Stationary Bar Code Label Printer with 802.11g/i Wireless Communications (Zebra P/N:123-100255) NOTE: Naval Surface Warfare Center, Dahlgren tested for Hazards of Electromagnetic Radiation to Ordnance (HERO) and the recommended safe distance separation is 12 inches..

**SUBCLIN 1009FA**

The CLIN extended description has changed from Stationary Bar Code and Gen2 RFID Label Printer/Encoder (Zebra P/N:RZ47D-2001-00R0) to Stationary Bar Code and Gen2 RFID Label Printer/Encoder (Zebra P/N:123-100256) NOTE: Naval Surface Warfare Center, Dahlgren tested for Hazards of Electromagnetic Radiation to Ordnance (HERO) and the recommended safe distance separation is 12 inches..

**SUBCLIN 1015AA**

The CLIN extended description has changed from Radio Frequency Access Point (indoor environment) includes: AP-7131 Dual Radio 802.11a/g Access Point (Motorola P/N:AP-7131N-44040-FGR ), [AP-7131 Power Supply: 100- 250VAC,48.0VDC, 0.75A (Motorola P/N: 50-14000-247R )], AC Line Cord (Motorola P/N: 50-16000-221R ), [Antenna: Indoor; Type: Dipole; 3dBi @2.4GHz (Motorola P/N: ML-2452-AP2-01)] to Radio Frequency Access Point (indoor environment) includes: AP-7131 Dual Radio 802.11a/g Access Point (Motorola P/N:AP-7131N-44040-FGR ), [AP-7131 Power Supply: 100- 250VAC,48.0VDC, 0.75A (Motorola P/N: 50-14000-247R )], AC Line Cord (Motorola P/N: 50-16000-221R ), [Antenna: Indoor; Type: Dipole; 3dBi @2.4GHz (Motorola P/N: ML-2452-AP2-01)] NOTE: Naval Surface Warfare Center, Dahlgren tested for Hazards of Electromagnetic Radiation to Ordnance (HERO) and the recommended safe distance separation is 14 inches..

**SUBCLIN 1015BA**

The CLIN extended description has changed from Radio Frequency Access Point (NEMA Enclosure) includes: AP-7131 Dual Radio 802.11a/g Access Point (Motorola P/N:AP-7131N-44040-FGR ), [AP-7131 Power Supply: 100- 250VAC,48.0VDC, 0.75A (Motorola P/N: 50-14000-247R )], AC Line Cord (Motorola P/N: 50-16000-221R ), NEMA Enclosure (TESSCO P/N:V14126-C60-C-6), RP-SMA (Male) to RP-BNC (Female) Adapter (Motorola P/N:25-72178-01), [Antenna: Indoor/Outdoor; Type: Dipole; 4.6dBi (Motorola P/N:ML-2499-HPA3-01R)] to Radio Frequency Access Point (NEMA Enclosure) includes: AP-7131 Dual Radio 802.11a/g Access Point (Motorola P/N:AP-7131N-44040-FGR ), [AP-7131 Power Supply: 100- 250VAC,48.0VDC, 0.75A (Motorola P/N: 50-14000-247R )], AC Line Cord (Motorola P/N: 50-16000-221R ), NEMA Enclosure (TESSCO P/N:V14126-C60-C-6), RP-SMA (Male) to RP-BNC (Female) Adapter (Motorola P/N:25-72178-01), [Antenna: Indoor/Outdoor; Type: Dipole; 4.6dBi (Motorola P/N:ML-2499-HPA3-01R)] NOTE: Naval Surface Warfare Center, Dahlgren tested for Hazards of Electromagnetic Radiation to Ordnance (HERO) and the recommended safe distance separation is 14 inches..

**SUBCLIN 1015CA**

The CLIN extended description has changed from Radio Frequency Gateway includes: AP-7131 Dual Radio 802.11a/g Access Point (Motorola P/N:AP-7131N-44040-FGR ), [AP-7131 Power Supply: 100-

250VAC,48.0VDC, 0.75A (Motorola P/N: 50-14000-247R ), AC Line Cord (Motorola P/N: 50-16000-221R ), RFMS Server Software (includes LANPlanner) (Motorola P/N:SW-RFMS-SRV-050-WW ), [Antenna: Indoor; Type: Dipole; 3dBi @2.4GHz (Motorola P/N:ML-2452-APA2-01 )] to Radio Frequency Gateway includes: AP-7131 Dual Radio 802.11a/g Access Point (Motorola P/N:AP-7131N-44040-FGR ), [AP-7131 Power Supply: 100-250VAC,48.0VDC, 0.75A (Motorola P/N: 50-14000-247R ), AC Line Cord (Motorola P/N: 50-16000-221R ), RFMS Server Software (includes LANPlanner) (Motorola P/N:SW-RFMS-SRV-050-WW ), [Antenna: Indoor; Type: Dipole; 3dBi @2.4GHz (Motorola P/N:ML-2452-APA2-01)] NOTE: Naval Surface Warfare Center, Dahlgren tested for Hazards of Electromagnetic Radiation to Ordnance (HERO) and the recommended safe distance separation is 14 inches..

(End of Summary of Changes)